



HX 3000

PORTABLE POWER

50Hz range Intens

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Compact frame with protection panels against shocks
- Solid and high-performance equipment

Divers

robustness, endurance and simple to use equipments for repetitive operations and in difficult conditions.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

HX 3000

GENERAL SPECIFICATIONS

Range	Intens
Frequency (Hz)	50
Max. power (LTP) (kW)	3
Max power. (LTP) (kVA)	3.75
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Guaranteed acoustic power Lw(A)	95
Noise level dB(A) - 1m	81
Noise level dB(A) - 7m	67

ENGINE SPECIFICATIONS

Engine trademark	Honda
Engine type	GX 200
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	2.4
Consumption (L/h]	1.3
Tank (L)	3.1
Oil Guard	Yes
Capacity (cm ³)	196
Oil capacity (L)	0.6

ALTERNATOR SPECIFICATIONS

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

Lenght (cm)	59
Width (cm)	46
Height (cm)	43
Dry Weight (kgs)	41

PACKAGING

Packaging type	Box
Length (cm)	60.5
Width (cm)	46
Height (cm)	44
Pallet type	140/110
Number of box by pallet	15
Pallet height (cm)	145

HX 3000 - PORTABLE POWER - 50Hz range Intens

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this CD Rom without notice, in a constant effort to improve the quality of its products.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

ACCESSORIES SUPPLIED



Funnel



User and maintenance manual

OPTIONS



R01 **Diferential protection R01** This set includes the hour meter and the differential circuit breaker.



R05M **Manual changeover switch** The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.



R06 **Trolley kit R06** Trolley kit for 2 and 3 kW generating sets.



R15 **R15 Quick Lock** This reel is specially designed for your SDMO generator set with a 20 m cable (3 x 1.52H07-RNF) to provide great freedom of movement. It has a safety plug with a 30 mA earth fault protection and a circuit breaker built into the reel.



R18 **Maintenance kit for HONDA engines R18** 10 maintenance kits for Honda GX160 and GX200 engine (except SH2500, Alizé 3000 et SH3000)



RBH1 **Cans of oil RBH1** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5 **Cans of oil RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RHO **Protection cover RHO** Cover for SDMO generator sets and petrol or diesel driven pumps



RPM **300 RPM** Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ **Earth spike RPQ** For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.